

<b>Model Name</b>	<b>BC-50</b>
<b>Product Name</b>	<b>IP Block Camera</b>
<b>Video format</b>	1080p 60/50/30/25 1080i 60/50 720p 60/50
<b>Image Sensor</b>	1/2.7" progressive scan CMOS sensor
<b>Effective Pixels (approx.)</b>	2.07 Mega pixels
<b>S/N Ratio</b>	55 dB
<b>Min. Illumination</b>	0.05 Lux @ (F1.8, AGC ON)
<b>Electronic Shutter</b>	1/30s ~ 1/10000s
<b>Zoom Ratio</b>	20x Optical zoom ; 16x Digital zoom
<b>Gamma Control</b>	Yes
<b>Iris Control</b>	Auto/Manual
<b>Digital Noise Reductions</b>	2D & 3D
<b>On-Screen Display (OSD)</b>	English, Simplified Chinese, Traditional Chinese
<b>White Balance</b>	Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K_1, 6500K_2, 6500K_3, One Push, Manual
<b>AGC / Gain Control</b>	Auto / Manual (0 to 28 step) Max. Gain Limit (6 to 28 step)
<b>Mirror / Flip Image</b>	Yes
<b>Focus Mode</b>	Auto / Manual
<b>Panning/Tilting Range</b>	N/A
<b>Panning/Tilting Speed</b>	N/A
<b>Preset</b>	N/A
<b>Field of View (Horizontal, Wide)</b>	Approx. 63.7° (WIDE END) / 2.3° (TELE END)
<b>Image Compensation</b>	Day & Night function
<b>Video Output</b>	3G/HD-SDI x1
<b>Tally LED</b>	Dual color (Red, Green)
<b>Filter</b>	M52.0 x 0.75 Thread with UV Protection
<b>RoHS</b>	Compliant

<b>Protocol</b>	VISCA, Pelco-D, Pelco-C
<b>Remote Control Interface and Transmit Distance</b>	RS-485: Transmit up to 1000m
<b>F/W Update</b>	Ethernet
<b>IR Control</b>	N/A
<b>Camera Control Unit</b>	N/A
<b>Size of Screw Hole for Tripod</b>	Use cold shoe mount
<b>Options</b>	PTR-10 Robotic Pan Tilt Head
<b>Color</b>	Dark Blue